



TYPICAL APPLICATIONS

Bituminous resurfacing  
Milling operations  
Utility operations  
Shoulder operations

SYMBOLS

- Work area
- Sign on portable or permanent support
- Flagger with traffic control sign

① Minimum distance is 60 m (200'). Maximum distance to be determined by the Engineer but should not exceed 1/2 the length required for one normal working day's operation or 3200 m (2 miles), which ever is less.

GENERAL NOTES

This Standard is used where at any time, any vehicle, equipment, workers or their activities require an intermittent or continuous moving operation on the pavement where the average speed of movement is greater than 2 km/h (1 mph) and less than 6 km/h (4 mph).

When the operation does not exceed 60 minutes, traffic control may be according to Standard 701301.

All dimensions are in millimeters (inches) unless otherwise shown.

Illinois Department of Transportation

APPROVED January 1, 2005

ENGINEER OF OPERATIONS

APPROVED January 1, 2005

ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

| DATE   | REVISIONS   |
|--------|---|
| 1-1-05 | Deleted FLAGGER SYMBOL sign and revised sign spacing. |
| 1-1-97 | Renum. Standard 2306-10.                              |
|        | Deleted orange flags and FRESH OIL sign.              |

LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS > 45 MPH

STANDARD 701306-01